

Incoflex AluPet Tape

Incoflex® Alupet Tape is a premium aluminum foil tape reinforced with PET film backing, combined with a strong solvent acrylic adhesive and comes with or without liner for quick and efficient application.

Designed for use with Incoflex XLPE insulation, it provides reliable coverage for joints. The tape is ideal for lap joints, face-to-face joints, and corner joints, ensuring secure and durable sealing.

Applications


Incoflex Alupet Tape is specially designed for use insulation system. It is suitable for all types of joints and fittings in piping and ducting applications within buildings.

As a Pressure Sensitive Adhesive (PSA) tape, proper pressure must be applied during installation to ensure secure adhesion and long-lasting performance.



Product Specification

Properties	Specification	Standards
Backing thickness	20 micron	D3652
Total thickness	55 micron	D3652
Adhesion to steel	15 N/25mm	D3330
Tensile strength	70 N/25mm	D3759
Elongation at break	20%	D3759
Tack Rolling Ball	10cm	D3121
Service Temperature	-30 ~ +100°C	
Apply Temperature	+10 ~ 40 °C	



Standard Sizes

W(mm)	L(Yds)	Rolls/Box
48	30	24
72	30	16
96	30	12

Custom sizes can be produced as per customer specifications

PACKING

Backing	Adhesive	Color	Liner
Foil with PET film reinforced	Solvent	Dull silver	With/Without Liner

STORAGE

Store under normal room temperature and 50% RH in the original packaging.

SHELF LIFE

Use within 12 months